


# DALI One Channel Relay Unit

## Model No.: DH1

AC input / 1 DALI address / dry contact output

### Features

- 1 DALI address, 1 channel 10 A dry contact mains rated relay output.
- Powered by AC100-240V.
- DALI-2 certified, in accordance with DALI standard protocol IEC 62386-101, 102, 208 and in compliance with DALI products from other international incorporation.
- Compliant DALI device type 7.
- High-inrush specification relays (single pole, normally open).
- Zero cross switching function.




CE RoHS LVD


### Technical Parameters

Input and Output		Environment		Safety and EMC	
Input voltage	100-240VAC	Operation temperature	Ta: -30°C ~ +55°C	EMC standard (EMC)	ETSI EN 301 489-1 V2.2.3 ETSI EN 301 489-17 V3.2.4
Input current	0.02A	Case temperature (Max.)	Tc: +60°C	Safety standard(LVD)	EN 62368-1:2020+A11:2020
Relay contacts	single-pole, single-throw (SPST) relay.	IP rating	IP20	Certification	CE, EMC, LVD
Max relay load current	10A resistive load 8A incandescent 5A inductive load	<b>Warranty</b>		<b>Package</b>	
		Warranty	5 years	Size	W135x L40 x H23mm
				Gross weight	0.089kg

### Mechanical Structures and Installations



### Wiring Diagram



### Operation

#### DALI address assigned by DALI masters

DALI address can also be assigned by DALI Master controller automatically.

Please refer to user manuals of compatible DALI Masters for specific operations.